

Resistance Wire for Low Temp Heating or Resistors Nickel-Copper Alloy - A30

$$in^2/\Omega = \frac{I^2 C_t}{p}$$

I = Current
C_t = Temperature factor
p = Surface load W/in²

Common Names: Alloy 30, CuNi 30, 30 Alloy, MWS-30, Cuprothal 30, HAI-30, Cu-Ni 2, Alloy 230, Nickel Alloy 30

Uses: Alloy exhibits low resistivity and high temperature coefficient of resistance. Typical applications include voltage regulators, timing devices, temperature sensitive resistors, temperature compensating devices, motor control, heating wires and cables, precision and vitreous resistors, potentiometers, and low temperature heating applications.

Composition

| Ni | Cr | Fe | Al | Si | Mn | Cu | C | Ti | Mo | W |
|----|------------|------------|------------|------------|------------|-----|------------|------------|------------|------------|
| 2% | None/Trace | None/Trace | None/Trace | None/Trace | None/Trace | 98% | None/Trace | None/Trace | None/Trace | None/Trace |

Technical Data

| | | | |
|------------------------------|--------------|--|----------------------|
| Resistivity (Ω/cm) | 30 | Resistivity (Ω/sqmf) | 24 |
| Resistivity (μΩ/cm) | 4.99 | Nom. Temp. Coeff. of Resistance (TCR) | 0.00130 |
| Std. Res. Tol. <.020" | 3% | Std. Res. Tol. >.020" | 5% |
| Thermal EMF vs. Cu | -0.014 | Specific Heat (20°C) | 0.092 cal/g |
| Density (g/cm ³) | 8.89 | Density (lb/in ³) | 0.321 |
| Thermal Conductivity | 1.16 W/cm/°C | Coeff. of Linear Expansion (X 10 ⁻⁶) | 16.40 in/in/°C |
| Approx. Melting Point | 1190°C | Max. Continuous Operating Temp. | 300°C |
| UTS – Hard (KPSI) | 60 | YTS Tensile – Hard (KPSI) | |
| UTS – Stress Relieved (KPSI) | | YTS Tensile – Stress Relieved (KPSI) | |
| UTS – Annealed (KPSI) | 30 | YTS Tensile – Annealed (KPSI) | |
| Magnetic Attraction | None | Emissivity – fully oxidized | |
| Designations/Specifications | ASTM = B267 | Forms Available | Wire, Ribbon, Insul. |

Temperature Factor – To obtain resistance at working temperature multiply by the factor C_t, in the following table:

| °C | 100 | 200 | 300 | 400 |
|--------------------|------|------|------|------|
| A30 C _t | 1.00 | 1.11 | 1.25 | 1.40 |

Alloy Data

| Diameter mm | Resistance at 20° C Ω/m | Resistance at 20° C Ω/kg | Weight kg/1000 m | Surface area cm ² /m | cm ² /Ω at 20°C |
|-------------|-------------------------|--------------------------|------------------|---------------------------------|----------------------------|
| 10.4049 | 0.0006 | 0.0008 | 755.5052 | 326.8804 | 557305.2014 |
| 9.2658 | 0.0007 | 0.0012 | 599.1420 | 291.0952 | 393578.6775 |
| 8.2515 | 0.0009 | 0.0020 | 475.1405 | 259.2276 | 277952.1436 |
| 7.3481 | 0.0012 | 0.0031 | 376.8030 | 230.8486 | 196294.6637 |
| 6.5437 | 0.0015 | 0.0050 | 298.8180 | 205.5765 | 138626.7237 |
| 5.8273 | 0.0019 | 0.0079 | 236.9731 | 183.0710 | 97900.6161 |
| 5.1894 | 0.0024 | 0.0125 | 187.9279 | 163.0293 | 69139.1268 |
| 4.6213 | 0.0030 | 0.0200 | 149.0334 | 145.1817 | 48827.2602 |
| 4.1154 | 0.0037 | 0.0317 | 118.1887 | 129.2880 | 34482.6649 |
| 3.6648 | 0.0047 | 0.0504 | 93.7278 | 115.1342 | 24352.2609 |
| 3.2636 | 0.0060 | 0.0802 | 74.3294 | 102.5299 | 17197.9924 |
| 2.9063 | 0.0075 | 0.1275 | 58.9458 | 91.3054 | 12145.5229 |
| 2.5882 | 0.0095 | 0.2028 | 46.7461 | 81.3098 | 8577.3807 |
| 2.3048 | 0.0120 | 0.3224 | 37.0713 | 72.4084 | 6057.4962 |
| 2.0525 | 0.0151 | 0.5127 | 29.3988 | 64.4815 | 4277.9097 |
| 1.8278 | 0.0190 | 0.8152 | 23.3143 | 57.4224 | 3021.1346 |
| 1.7249 | 0.0213 | 1.0280 | 20.7620 | 54.1881 | 2538.8633 |
| 1.6277 | 0.0240 | 1.2963 | 18.4890 | 51.1361 | 2133.5781 |
| 1.5360 | 0.0269 | 1.6346 | 16.4650 | 48.2559 | 1792.9896 |
| 1.4495 | 0.0302 | 2.0612 | 14.6625 | 45.5380 | 1506.7702 |

| Diameter mm | Resistance at 20° C Ω/m | Resistance at 20° C Ω/kg | Weight kg/1000 m | Surface area cm ² /m | cm ² /Ω at 20°C |
|-------------|-------------------------|--------------------------|------------------|---------------------------------|----------------------------|
| 1.3679 | 0.0339 | 2.5991 | 13.0573 | 42.9731 | 1266.2406 |
| 1.2908 | 0.0381 | 3.2774 | 11.6278 | 40.5527 | 1064.1074 |
| 1.2181 | 0.0428 | 4.1328 | 10.3549 | 38.2686 | 894.2413 |
| 1.1495 | 0.0481 | 5.2114 | 9.2213 | 36.1132 | 751.4913 |
| 1.0848 | 0.0540 | 6.5714 | 8.2118 | 34.0792 | 631.5288 |
| 1.0237 | 0.0606 | 8.2864 | 7.3128 | 32.1597 | 530.7163 |
| 0.9660 | 0.0680 | 10.4490 | 6.5122 | 30.3483 | 445.9967 |
| 0.9116 | 0.0764 | 13.1759 | 5.7993 | 28.6390 | 374.8011 |
| 0.8603 | 0.0858 | 16.6146 | 5.1644 | 27.0260 | 314.9707 |
| 0.8118 | 0.0964 | 20.9506 | 4.5991 | 25.5038 | 264.6911 |
| 0.7661 | 0.1082 | 26.4183 | 4.0956 | 24.0673 | 222.4378 |
| 0.7229 | 0.1215 | 33.3129 | 3.6472 | 22.7117 | 186.9295 |
| 0.6822 | 0.1364 | 42.0068 | 3.2479 | 21.4325 | 157.0895 |
| 0.6438 | 0.1532 | 52.9697 | 2.8924 | 20.2254 | 132.0129 |
| 0.6075 | 0.1720 | 66.7936 | 2.5757 | 19.0862 | 110.9393 |
| 0.5733 | 0.1932 | 84.2253 | 2.2937 | 18.0112 | 93.2298 |
| 0.5410 | 0.2169 | 106.2063 | 2.0426 | 16.9967 | 78.3473 |
| 0.5106 | 0.2436 | 133.9239 | 1.8190 | 16.0394 | 65.8405 |
| 0.4818 | 0.2736 | 168.8752 | 1.6199 | 15.1360 | 55.3302 |
| 0.4547 | 0.3072 | 212.9480 | 1.4425 | 14.2835 | 46.4977 |
| 0.4291 | 0.3450 | 268.5228 | 1.2846 | 13.4790 | 39.0752 |
| 0.4049 | 0.3874 | 338.6015 | 1.1440 | 12.7198 | 32.8375 |
| 0.3821 | 0.4350 | 426.9692 | 1.0188 | 12.0034 | 27.5956 |
| 0.3606 | 0.4884 | 538.3990 | 0.9072 | 11.3273 | 23.1904 |
| 0.3403 | 0.5485 | 678.9096 | 0.8079 | 10.6893 | 19.4885 |
| 0.3211 | 0.6159 | 856.0905 | 0.7195 | 10.0873 | 16.3775 |
| 0.2859 | 0.7767 | 1361.2411 | 0.5706 | 8.9830 | 11.5661 |
| 0.2546 | 0.9794 | 2164.4643 | 0.4525 | 7.9996 | 8.1682 |
| 0.2268 | 1.2350 | 3441.6428 | 0.3588 | 7.1238 | 5.7685 |
| 0.2019 | 1.5572 | 5472.4421 | 0.2846 | 6.3439 | 4.0738 |
| 0.1798 | 1.9637 | 8701.5487 | 0.2257 | 5.6494 | 2.8770 |
| 0.1601 | 2.4761 | 13836.0441 | 0.1790 | 5.0310 | 2.0318 |
| 0.1426 | 3.1223 | 22000.2348 | 0.1419 | 4.4802 | 1.4349 |
| 0.1270 | 3.9372 | 34981.8437 | 0.1125 | 3.9897 | 1.0133 |
| 0.1131 | 4.9647 | 55623.4694 | 0.0893 | 3.5529 | 0.7156 |
| 0.1007 | 6.2604 | 88445.0339 | 0.0708 | 3.1640 | 0.5054 |
| 0.0897 | 7.8943 | 140633.5151 | 0.0561 | 2.8176 | 0.3569 |
| 0.0799 | 9.9545 | 223616.6882 | 0.0445 | 2.5092 | 0.2521 |
| 0.0711 | 12.5524 | 355565.4794 | 0.0353 | 2.2345 | 0.1780 |
| 0.0633 | 15.8283 | 565372.8762 | 0.0280 | 1.9898 | 0.1257 |
| 0.0564 | 19.9591 | 898980.6594 | 0.0222 | 1.7720 | 0.0888 |
| 0.0502 | 25.1680 | 1429439.3310 | 0.0176 | 1.5780 | 0.0627 |
| 0.0447 | 31.7364 | 2272904.0717 | 0.0140 | 1.4053 | 0.0443 |
| 0.0398 | 40.0189 | 3614069.3817 | 0.0111 | 1.2514 | 0.0313 |
| 0.0355 | 50.4629 | 5746611.8603 | 0.0088 | 1.1144 | 0.0221 |
| 0.0316 | 63.6327 | 9137496.9279 | 0.0070 | 0.9924 | 0.0156 |
| 0.0281 | 80.2394 | 14529230.8125 | 0.0055 | 0.8838 | 0.0110 |
| 0.0251 | 101.1802 | 23102448.0410 | 0.0044 | 0.7870 | 0.0078 |

Information presentation property of Hyndman Industrial Products, Inc., 3205 Cannongate Drive, Fort Wayne, IN 46808-4518, 888.496.3626, www.resistancewire.com

(Disclaimer) This information is provided for information purposes only "As is." Hyndman Industrial Products, Inc. makes no warranty of any kind with respect to the subject matter or accuracy of the information. Hyndman Industrial Products, Inc. specifically disclaims all warranties, expressed, implied or otherwise, including without limitation, all warranties of merchantability and fitness for a particular purpose. This publication may include technical inaccuracies or typographical errors; changes may be made to the information herein. If errors are found, please submit the correction via e-mail to: webmaster@resistancewire.com. Include correction, and page address if possible. All trademarks referenced are the property of their respective owners. Ownership can be researched at www.marksonline.com or by contacting Hyndman Industrial Products, Inc.